


# Additional Data Sheet

## Configuration

Lowest temperature applied:	-20 °C
-----------------------------	--------

### ATP registration numbers of vehicle

Manufacturer brand	Krone
Vehicle identification no.	100551
ATP type approval no.	3797T
Floor material	Al/ Wood 0,125 m
ATP type approval no. of refr. unit	P430U/24
Brand Host Unit	A500S
Serial number of Host Unit	GLW1530418
Brand additional evaporator	S-3
Serial number of additional evaporator	GLW1529851



Data of overall body	Internal dimensions			K value of outer body 0,380 W/m²K
	L	W	H	
	13,410m	2,460m	2,700 m	
	External dimensions			
	13,547m	2,600m	2,915m	

## A. Input data


### A1. Data of insulated body

Data of internal bulkheads	Movable or fixed	Thickness	K value [W/m².°C]
Transversal bulkhead (1→2)	movable	43,0 mm	3,2

Dimensions / Use of Compartments	Internal length		Fixed temperature in each comp.?	Compartment temperature	Dry freight use?	Lowest class temp. permitted in each comp.?	Lowest permitted temp. per comp.
	Minimal length	Maximal length					
Compartment 1	8,290 m	10,970 m	No		Yes	Yes	
Compartment 2	2,400 m	5,080 m					

### A2. Data of multitemp refrigeration unit

Cooling capacities at:	-20 °C
Nominal refr. cap. host unit	10004 W
Individual refr. cap. evap. 1	8730 W
Individual refr. cap. evap. 2	5609 W



Le / on : 2026/05/21



Adresse:  
5 avenue des prés  
CS20029  
94266 - Fresnes  
France

+33 (0) 1 49 84 84 84  
contact@cemafröid.fr

Cemafröid SAS  
Responsable ATP / Responsible for the ATP

Le Président de CEMAFRÖID SAS

TECNEA SAS représentée par son Président Gérald CAVALIER

DC-02210675-00980534-1514501ATPD0626016285